



Ultrahigh-speed hybrid laser for silicon photonic integrated chips

Chung, Il-Sug; Park, Gyeong Cheol; Ran, Qijiang; Semenova, Elizaveta; Yvind, Kresten; Mørk, Jesper

Published in:
NANO KOREA 2013

Publication date:
2013

[Link back to DTU Orbit](#)

Citation (APA):
Chung, I-S., Park, G. C., Ran, Q., Semenova, E., Yvind, K., & Mørk, J. (2013). Ultrahigh-speed hybrid laser for silicon photonic integrated chips. In *NANO KOREA 2013*

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Ultrahigh-speed hybrid laser for silicon photonic integrated chips

Il-Sug Chung*, Gyeong Cheol Park, Qijiang Ran, Elizaveta Semenova, Kresten Yvind, and
Jesper Mørk

Department of Photonics Engineering, Technical University of Denmark, DK-2800 Kgs. Lyngby, Denmark

**E-mail address: ilch@fotonik.dtu.dk*

Increasing power consumption for electrical interconnects between and inside chips is posing a real challenge to continue the performance scaling of processors/computers as predicted by D. Moore. In recent processors, energy consumption for electrical interconnects is half of power supplied and will be 80% in near future. This challenge strongly has motivated replacing electrical interconnects with optical ones even in chip level communications [1]. This chip-level optical interconnects need quite different performance of optoelectronic devices than required for conventional optical communications. For a light source, the energy consumption per sending a bit is required to be <10 fJ/bit for on-chip interconnects and <100 fJ/bit for off-chip interconnects; this is two or three orders of magnitude smaller than the conventional devices. To meet the energy/bit requirement, many innovative laser diode and light-emitting diode (LED) structures have been proposed so far. Our hybrid laser is one of these efforts [2].

The hybrid laser consists of a dielectric reflector, a III-V semiconductor active material, and a high-index-contrast grating (HCG) reflector formed in the silicon layer of a silicon-on-insulator (SOI) wafer. ‘Hybrid’ indicates that a III-V active material is wafer-bonded to a silicon SOI wafer. In the hybrid laser, light is vertically amplified between the dielectric and the HCG reflectors, while the light output is laterally emitted to a normal Si ridge waveguide that is connected to the HCG reflector. The HCG works as a vertical mirror as well as a vertical-to-lateral coupler. Very small field penetration into the HCG allows for 3-4 times smaller modal volume than typical vertical-cavity surface-emitting lasers (VCSELs). This leads to high direct modulation speed. Details on device operating mechanism will be explained in the lecture.

Recently, a nano light-emitting diode (LED) with energy/bit < 1 fJ/bit [3] and a nano laser diode with a buried heterostructure (BH) active material [4] have been recently reported in the literature. Additionally, device physics, engineering issue, and error-free light detection issue in quantum limit will be discussed in relation to these two structures.

References

1. D. Miller, Proc. IEEE **97**, 1166 (2009).
2. I.-S. Chung and J. Mørk, J., Appl. Phys. Lett. **97**, 151113 (2010).
3. G. Shambat et al., Nat. Communications **2**, 539 (2011).
4. S. Matsuo et al., Opt. Express **20**, 3773 (2012).